

Usage Instructions

1. **COLD WATER Dispensing:**
 - o Push Down COLD Lever to dispense water
2. **HOT WATER Dispensing:**
 - o Pull & Hold Safety button then push down HOT Lever to dispense water
3. **AMBIENT WATER Dispensing:**
 - o Push Down AMBIENT Lever to dispense water

Dimensions

CLIMA Piso:



Technical Specification

Description	CLIMA Piso
Recommended Serving PAX	Up to 15-30
Temperature	75 °c ~ 100 °c
Tank Capacity	5L (HOT) 3L (COLD) Unlimited (AMBIENT)
Unit Height (mm)	1160
Unit Width (mm)	280
Unit Depth (mm)	530
Electrical Specifications	AC200 – 240V: 50 – 60Hz Heating Power: 750W Cooling Power: 170W
Weight	35kg
Origin	Taiwan

Support & General Maintenance

Cleaning Instructions Dispenser:

Use a damp cloth to wipe the surfaces – Do not use cleaning agents that may cause discolouration and corrosion to the plated surfaces.

Troubleshooting

Leakage:

In the unlikely event of leakage, turn off the power supply and water valve supplying water to the modules and contact our Technical Support.

Recommendations:

If water filtration unit is left unused for more than 2 days due to e.g. overseas travels, office closure etc., we highly recommend the following:

- Turn off the water inlet valve supplying water to the filtration
- When turning it back on for use, flush out the stagnant water within the system by turning on the tap for at least 2 minutes before consumption

Do not store hazardous chemical by-products such as cleaning agents and pesticides near the filtration system, so as to prevent any possible contamination.

Swisspro Pte Ltd

15 Jalan Kilang Barat
Frontech Centre #04-07
Singapore 159357

Tel: +65 6276 1005

Fax: +65 6276 1504

Website: www.swisspro.sg, www.swissprowater.com